

Features:

- **Pulseless**
Flow Stabilization to $\pm 2\%$.
- **Accurate**
New Valve Designs Increase Precision.
 $\pm 0.5\%$ Over 10:1 Range.
- **Compact**
Single Drive Housing With Two Heads.
Vertical Motor Mounting.

The NIKKISO MILFLO Series 6000 is a pulseless metering pump which incorporates a unique, innovative, drive cam design and high precision check valve configuration. This combination delivers higher accuracy and better flow stabilization in a more compact format.



Performance Table			
Capacity Range (GPH)	Maximum Pressure (PSIG)	Speed Range (SPM)	Plunger Diameter (mm)
0.02 - 0.25	710	6 - 60	3.2
0.06 - 0.62	710	6 - 60	5
0.12 - 1.21	710	6 - 60	7
0.25 - 2.54	710	6 - 60	10
0.50 - 5.00	455	6 - 60	14
1.03 - 10.3	230	6 - 60	20
2.01 - 20.1	115	6 - 60	28

Special features setting this pump apart are:

- New drive cam design which delivers constant forward plunger velocity and extended discharge duration to create pulseless flow.
- High precision plunger to cam coupling to more accurately control plunger travel.
- Specially designed check valves with reduced cycle time for more precise metering.
- Utilization of proven liquid end components in a modular format providing interchangeability across the NIKKISO product platform.
- Compact configuration achieved by mounting the motor on top of the pump and a single drive cam which controls both plungers.
- Elimination of motor alignment procedures due to the use of a standard c-face motor.
- Reduced preventative maintenance with a totally submerged drive oil bath which greatly extends the life of the pump drive.

Custom Features	Accessories
Alternate Materials of Construction	NIKKISO HydroChek™ Calibration Columns
API 675 & HI Standards Compliant	NIKKISO HydroDamp® Pulsation Dampeners
Automatic Capacity Control	NIKKISO HydroDrive™ VSD's and Motor Controls
Double Diaphragm Liquid Ends	NIKKISO HydroGarD™ Valves
Diaphragm Status Indication	NIKKISO HydroInjex™ Injection Assemblies
Liquid End Jacketing	NIKKISO HydroMix™ Agitators
Sanitary Configuration	NIKKISO HydroTank® Liquid Handling Packages

Component	Materials of Construction			
Pumphead	316SS	Alloy 20	Hastelloy® C	Special
Check Valve Body	316SS	Alloy 20	Hastelloy® C	Special
Check Valve Seat	316SS	Alloy 20	Hastelloy® C	Special
Check Valve Element	316SS	Alloy 20	Hastelloy® C	Special
Diaphragm	PTFE	PTFE	PTFE	Special
Plunger	316SS	Alloy 20	Hastelloy® C	Special
Packing	PTFE	PTFE	PTFE	Special

